



Config Table

SKU#	Power Cord Length	Plug/Power Cord
AP1101	-	-
AP1101-20P	25mm ² x3, 2M	IEC320 C19 - IEC309 16A 3P6H IP44 PLUG



IEC320 INPUT
16A

PUD Series: Basic
 Input: 200-240V AC, 16A, 1Ph
 CB/Bank: 1xBank
 Outlet: C13 [14], C19 [2].
 Outlet Color: Black
 Chassics Color: Black

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF A-RACK AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM A-RACK. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

Drawn by	Description	Drawing No.	
Approved by	Basic PDU, 200-240V AC, 16A, 1Ph C13 [14], C19 [2]	AP11001	
	Version	Third Angle Projection	Unit: mm
	Scale: 1:-	A4	Sheet1 of 1

Tolerances/Tolerance
 ISD
 2768-M
 >0.5=3 ±0.1
 >3=6 ±0.1
 >6=30 ±0.2
 >30=120 ±0.3
 >120=400 ±0.5
 >400=1000 ±0.8