


Tolerances/Tolerance $\frac{1SD}{2768-M}$ $>0.5=3 \pm 0.1$ $>3=6 \pm 0.1$ $>6=30 \pm 0.2$ $>30=120 \pm 0.3$ $>120=400 \pm 0.5$ $>400=1000 \pm 0.8$

Config Table

SKU#	Power Cord Length	Plug
AP1103	-	-
AP1103-20	6mm ² x3, 2M	-
AP1103-20P	6mm ² x3, 2M	IEC309 32A 3P6H IP44

PUD Series: Basic
 Input: 200-240V AC, 32A, 1Ph
 Input power cord: 6mm² x3, 2M, IEC309 32A 6H 3L+N+E Plug
 CB/Bank: 16A/1P [2], 2xBank
 Outlet: C13 [42], C19 [6].
 Outlet Color: Black/RED
 Chassics Color: Black



IEC609 PLUG
IP44 32A 3P6H

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF A-RACK AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM A-RACK. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

Drawn by	Description	Drawing No.	
Approved by	Basic PDU, 200-240V AC, 32A 1Ph C13 [42], C19 [6]	AP11003	
	Version	Third Angle Projection	Unit: mm
	Scale:	A1 1:-	A4 Sheet1 OF 1